

Bulk Fill Containment Fill Station

The Fills Without The Frills.



Our Bulk Fill, Non-Cascade Containment Fill Stations offer efficient SCBA/SCUBA filling with minimal manual intervention, ideal for operators seeking a simplified filling process.



**Straightforward
Operation**

ARCTIC
COMPRESSOR

**Exceeds
NFPA
Standards***



Product Comparison

Model	Fill Positions	Max Pressure	Series
C-FS1-55	1	6000 PSI	Bulk Fill Series
C-FS2-55	2	6000 PSI	
C-FS3-55	3	6000 PSI	
C-FS1C55	1	6000 PSI	Manual Cascade Series
C-FS2C55	2	6000 PSI	
C-FS2C55	3	6000 PSI	
C-FS2PA55	2	6000 PSI	Auto-Cascade Series
C-FS3PA55	3	6000 PSI	
C-2FS MOBILE	2	6000 PSI	Compact Series

Warranty

All Arctic Containment Fill Stations come with a standard 2-year warranty. Extend your coverage up to 5 years with our Gold Warranty option.



Truly American-Made™

Reliability. Dependability. Simple.

Quality Design



Strong and Safe

We build with high-grade steel and aircraft-grade aluminum components to be the most durable, longest-lasting fill station on the market. Designed with maximum operator safety in mind with our interlock system, secure latching mechanism, and vented design.



High-Pressure

Our control panels and isolation fill valve systems enable efficient filling and monitoring of multiple cylinders.



Operator Friendly Focus

All our fill stations come standard with well-balanced doors equipped with gas strut assistance for easy single-handed operation, while durable coated fill pockets prevent cylinder scuffing.

What's Included

Exceptional Safety

- **Safety Interlock**
Prevents filling unless door is closed and latched
- **Lockout Capabilities**
Latching mechanism provides lockout capabilities
- **Venting**
Vents are at the back and bottom of the unit for operator safety
- **Fabricated Steel Cabinet and Door**
Unit is constructed from high-strength steel

Ergonomic & Efficient Operation

- **Single-Handed Loading**
Balanced door design with gas strut assistance for easy, single-handed operation

Real-Time Monitoring

- **Pressure Gauges**
Glycerin filled pressure gauges with both PSI and BAR scales
- **Isolation Fill Valves**
Individual isolation fill valves provide operator control

Easy Connections

- **Simple Filling**
Fill hoses with bleed valves and SCBA fill adapter
- **Cylinder Adaptability**
Ability to accommodate most 2216 PSI to 5500 PSI SCBA or SCUBA cylinders

Dimensions



Model	Fill Positions	Width	Height	Depth	Weight
C-FS1-55	1	21"	47"	21"	400lbs
C-FS2-55	2	30"	47"	21"	590lbs
C-FS3-55	3	42"	47"	21"	780lbs

*Tested to withstand 5700 PSI burst pressure, exceeding NFPA 1901 (2016) 24.9.6.2 requirements of 5500 PSI.



69 North 28th Street,
Suite #500
Superior, WI 54880

(715) 718 - 3065
ArcticCompressor.com