Open Frame Compressor Series

Open Frame, Outstanding Quality.


Arctic Open Frame Compressors deliver up to 9 CFM at 6000 PSI and come standard with excellent durability, easy maintenance, and superior cooling in a more compact package.



Enhanced
Airflow for
Optimal Cooling



Easy Component Access





Made in the USA



Product Comparison

Model	PSI	CFM	HP	Stages	Series	
E4-20-A6	6000	24	20	4	2500	
E4-15-A6	6000	18	15	4	Series	
E4-10-A6	6000	14	10	4	1500	
E4-7.5-A6	6000	9	7.5	4	Series	
E3-7.5-A6	6000	8	7.5	3	1000	
E3-7.5-A	5000	9	7.5	3	Series	
04-10-A6	6000	9	10	4		
03-7.5-A6	6000	8	7.5	3	Open Frame Series	
03-7.5-A	5000	9	7.5	3		

Electrical Requirements

All Arctic Compressors include an 8ft electrical cord and plug. Our Open Frame Compressors requires the following:

208/240V Connection				480V Connection		
Phase	НР	Connector	Amperage	Connector	Amperage	
3	7.5	NEMA L15-30	30 Amp	NEMA L16-20	20 Amp	
3	10	NEMA L15-30	30 Amp	NEMA L16-20	20 Amp	
1	7.5	NEMA 6-50	50 Amp			
1	10	NEMA 6-50	50 Amp			

Truly American-Made

Reliability. Dependability. Simple.



CGA Grade E Quality Breathing Air

Our compressors deliver CGA Grade E breathing air, the gold standard for respiratory safety. This premium air quality not only meets but **exceeds** the stringent requirements set by regulatory bodies.



Air Purification

Filtration Technology

- Activated charcoal removes harmful gases and odors
- · Carbon monoxide catalyst converts CO to harmless CO
- · Ensures highest level of air purity for safe breathing

Moisture Control

- Reliable dryer filter
- Maintains dew point at or below -65°F (NFPA 1500 compliant)
- · Prevents condensation and corrosion

What's Included

Moderate Noise Operation

92 dB Sound Level at 1 Meter

Easy Maintenance

- Automatic Condensate Drain System
- · Easy Oil Maintenance Accessibility

Powerful Motor

 High-Efficiency Single or Three-Phase Electric Motor

Simple Lubrication System

- Splash Lubrication Oil System
- · 3 qt Oil Capacity

Real-Time Monitoring

- Interstage Pressure Gauges
- Hour Meter

Durable Compressor Block

Radial Arctic Compressor Block, equipped with

- · 10-Bladed High Velocity Fan
- Relief Valve on All Stages
- Aluminum Intercoolers
- · Stainless Steel Aftercoolers
- Forged Steel Crankshaft
- Cast Iron Cylinders

Optional Upgrades

- · Arctic M4200 CO Monitor
- Low Oil Auto Shutdown
- · High-Temp Auto Shutdown
- · Remote Start
- · Dual Pressure System
- Additional Filtration Capacity

Dimensions

Width

Height



Stages	Width	Height	Depth	Weight
3	48"	36"	20"	320lbs
4	48"	36 "	20"	410lbs



Warranty

All Arctic Compressors come with a standard 2-year warranty. Extend your coverage up to 5 years with our Silver or Gold Warranty options.



69 North 28th Street, Suite #500 Superior, WI 54880

(715) 718 - 3065 ArcticCompressor.com